





















Index	Model No.	Product Description (IP Camera)	Photo
A VidoNet Fix Dome IP Camera			
1*	VN-VTC-D10	<p>VidoNet 1/3' CMOS 1.3MP/25FPS(1280 x 960)Indoor/Outdoor IR Mini Dome f=3.6mm @F1.2, Angle of View: 77° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 20M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
2	VN-VTC-D20	<p>VidoNet 1/ 2.7' CMOS 2MP/25FPS(1920 x 1080)Indoor/Outdoor IR Mini Dome f=3.6mm @F1.2, Angle of View: 77° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 20M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
3	VN-VTC-D40	<p>VidoNet 1/3' CMOS 4MP/25FPS(2688 x 1520)Indoor/Outdoor IR Mini Dome f=3.6mm @F1.2, Angle of View: 77° (Option 2.8mm / 98°) Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 20M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
4	VN-VTC-E20S <i>(New)Sony Starvis</i>	<p>1 / 2.8 "CMOS 2MP Network I R Water-proof Dome Camera Color : 0.002 lux @F1.2,AGC ON;B / W : 0.0002 lux @F1.2,AGC ON f = 2.8 mm @ F1.4, horizontal field of view : 107° Triple stream,IR distance 20M,ICR auto switch,true day /night,DWDR, IP66 ingress protection , Power Supply: 12VDC & PoE Input</p>	
5	VN-VTC-E30C	<p>VidoNet 1/ 2.8' CMOS 3MP/25FPS(2048 x 1536)Indoor/Outdoor IR Mini Dome f=2.8mm @F1.2, Angle of View: 98° Color: 0.1 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 20M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
6	VN-VTC-D50	<p>VidoNet 1/3' CMOS 5MP/25FPS(2590 x 1944)Indoor/Outdoor IR Mini Dome f=5mm @F2.2, Angle of View: 72° Color: 0.01 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Gigabit Ethernet Network Port (RJ45 x 1) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
7	VN-VTC-D80 4K	<p>VidoNet 1/3' CMOS 8MP/25FPS(3840 x 2160)Indoor/Outdoor IR Mini Dome f=5mm @F2.2, Angle of View: 77° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) Gigabit Ethernet Network Port (RJ45 x 1) IP66 & IK10 , DC12V,802.3af PoE</p>	

Index	Model No.	Product Description (IP Camera)	Photo
B	VidoNet Varifocal Dome IP Camera		Photo
1	VN-VTC-D11	<p>VidoNet 1/3' CMOS 1.3MP/25FPS(1280 x 960)Indoor/Outdoor IR Mini Dome f=2.8 - 12mm @F1.2, Angle of View: 98° - 33° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 20M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
2	VN-VTC-D21	<p>VidoNet 1/ 2.7' CMOS 2MP/25FPS(1920 x 1080)Indoor/Outdoor IR Mini Dome f=2.8 - 12mm @F2.2, Angle of View: 98° - 33° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 20M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
3	VN-VTC-D41	<p>VidoNet 1/3' CMOS 4MP/25FPS(2688 x 1520)Indoor/Outdoor IR Mini Dome f=3.3 - 12mm @F1.4, Angle of View: 80° - 38° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output , Support SD Card (Up to 64GB) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
4	VN-VTC-D41AF	<p>VidoNet 1/3' CMOS 4MP/25FPS(2688 x 1520)Indoor/Outdoor IR Mini Dome f=3.3 - 12mm @F1.4, Angle of View: 88° - 38° Wide Dynamic Range 120dB & Electrical zoom camera optional Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output , Support SD Card (Up to 128GB) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
5	VN-VTC-D51	<p>VidoNet 1/3' CMOS 5MP/25FPS(2590 x 1944)Indoor/Outdoor IR Mini Dome f=3.6 - 10mm @F1.4, Angle of View: 83.7° - 36.7° Color: 0.01 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output , Support SD Card (Up to 64GB) Gigabit Ethernet Network Port (RJ45 x 1) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	
6	VN-VTC-D81AF 4K	<p>VidoNet 1/ 2.5' CMOS 4MP/25FPS(2688 x 1520)Indoor/Outdoor IR Mini Dome f=3.3 - 12mm @F1.4, Angle of View: 97.5° - 38.5° Wide Dynamic Range 120dB & Electrical zoom camera optional Color: 0.01 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output , Support SD Card (Up to 128GB) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	





Index	Model No.	Product Description (IP Camera)	Photo
C	VidoNet Fix Bullet IP Camera		Photo
1*	VN-VTC-B10	<p>VidoNet 1/3' CMOS 1.3MP/25FPS(1280 x 960) Outdoor Bullet Camera f=3.6mm @F1.2, Angle of View: 77° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66, DC12V,802.3af PoE</p>	
2	VN-VTC-B20	<p>VidoNet 1/ 2.7' CMOS 2MP/25FPS(1920 x 1080) Outdoor Bullet Camera f=3.6mm @F1.2, Angle of View: 77° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66, DC12V,802.3af PoE</p>	
3	VN-VTC-B40	<p>VidoNet 1/3' CMOS 4MP/25FPS(2688 x 1520) Outdoor Bullet Camera f=3.6mm @F1.2, Angle of View: 77° (2.8mm Optional) Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 30M,ICR auto switch,true day /night,DWDR,CV Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66, DC12V,802.3af PoE</p>	
4*	VN-VTC-B20C	<p>VidoNet 1/ 2.8' CMOS 2MP/25FPS(1920 x 1080) Outdoor Bullet Camera F=3.6mm @F1.6, Angle of View: 79° Color: 0.1 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 20M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 ,802.3af PoE</p>	
5	VN-VTC-B20S <i>(New)Sony Starvis</i>	<p>1 / 2.8 "CMOS 2MP Network I R Water-proof Bullet Camera Color : 0.002 lux @F1.2,AGC ON;B / W : 0.0002 lux @F1.2,AGC ON f = 2.8 mm @ F1.4, horizontal field of view : 107° Triple stream,IR distance 20M,ICR auto switch,true day /night,DWDR, IP66 ingress protection Power Supply: 12VDC & PoE Input</p>	
6	VN-VTC-B30C	<p>VidoNet 1/3' CMOS 3MP/25FPS(2048 x 1536) Outdoor Bullet Camera f=2.8mm @F1.2, Angle of View: 98° Color: 0.1 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 20M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 ,802.3af PoE</p>	
7	VN-VTC-B50	<p>VidoNet 1/3' CMOS 5MP/25FPS(2592 x 1944) Outdoor Bullet Camera f=5mm @F2.2, Angle of View: 98° ~ 33° Color: 0.01 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 50M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output , Support SD Card (Up to 64GB) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 , DC12V,802.3af PoE</p>	
8	VN-VTC-B80 4K	<p>VidoNet 1/3' CMOS 8MP/25FPS(3840 x 2160) Outdoor Bullet Camera f=5mm @F2.2, Angle of View: 72° Color: 0.01 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output , Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 & IK10 , DC12V,802.3af PoE</p>	






Index	Model No.	Product Description (IP Camera)	Photo
D	VidoNet Varifocal Bullet IP Camera		Photo
1*	VN-VTC-B11	<p>VidoNet 1/3' CMOS 1.3MP/25FPS(1280 x 960) Outdoor Bullet Camera f=2.8 - 12mm @F1.2, Angle of View: 98° - 33° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66, DC12V,802.3af PoE</p>	
2	VN-VTC-B21	<p>VidoNet 1/ 2.7' CMOS 2MP/25FPS(1920 x 1080) Outdoor Bullet Camera f=2.8 - 12mm @F1.2, Angle of View: 98° - 33° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 30M,ICR auto switch,true day /night,DWDR, Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66, DC12V,802.3af PoE</p>	
3	VN-VTC-B41	<p>VidoNet 1/3' CMOS 4MP/25FPS(2688 x 1520) Outdoor Bullet Camera f=3.3 - 12mm @F1.4, Angle of View: 89° - 33° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Dual stream,IR distance 30M,ICR auto switch,true day /night,DWDR,CV Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66, DC12V,802.3af PoE</p>	
4	VN-VTC-B41AF	<p>VidoNet 1/3' CMOS 4MP/25FPS(2688 x 1520) Outdoor Bullet Camera f=3.3 - 12mm @F1.4, Angle of View: 80° - 38° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Wide Dynamic Range 120dB & Electrical zoom camera optional Triple stream,IR distance 50M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output ,Support SD Card (Up to 128GB) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66, DC12V,802.3af PoE</p>	
5	VN-VTC-B51	<p>VidoNet 1/3' CMOS 5MP/25FPS(2592 x 1944) Outdoor Bullet Camera f=3.6 - 10mm @F1.4, Angle of View: 83.7° - 36.7° Color: 0.01 Lux @F1.2, 0 Lux (IR LED ON) Triple stream,IR distance 50M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output , Support SD Card (Up to 64GB) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66 , DC12V,802.3af PoE</p>	
6	VN-VTC-B81AF 	<p>VidoNet 1/3' CMOS 8MP/25FPS(3840 x 2160) Outdoor Bullet Camera f=3.3 - 12mm @F1.4, Angle of View: 97.5° - 38.5° Color: 0.05 Lux @F1.2, 0 Lux (IR LED ON) Wide Dynamic Range 120dB & Electrical zoom camera optional Triple stream,IR distance 50M,ICR auto switch,true day /night,DWDR, Mic In/Out x 1, CVBS Output ,Support SD Card (Up to 128GB) Support P2P,Free APP for Android/iOS,NVMS(Management Paltform) IP66, DC12V,802.3af PoE</p>	





Index	Model No.	Product Description (IP Camera)	Photo
E	VidoNet Pinhole IP Camera		Photo
1	VN-VTC-PH20	<p>VidoNet 1/3' Sony Porgressive scan CMOS,2MP(1920 x 1080@25/30fps) f=3.7mm Lens,0.01Lux @ (F1.2, AGC ON) Support WDR>80dB,BLC, AWB, AGC Mini vandal proof dome housing G.726/G711A/G711U audio coding Day/Night IR Cut Filter , Audio & Alarm I/O, SD card Slot DC12V,802.3af PoE</p>	
F	VidoNet IP Speed Dome Camera		Photo
1	VN-VTC-S33-IR	<p>VidoNet 20x 3MP IR Network + AHD(2MP) Hybrid HD f=5.5 ~ 110 mm lens, F1.6 ~ F3.5 Color:0.05 Lux @F1.2,AGC ON/B/W: 0.01Lux @F1.2,AGC ON,0Lux(IR LED ON) 20x Optical zoom ,360° endless rotation , 90m IR Night view distance SD card local storage/Dual Stream/Mic in x 1/Mic out x 1 IP66 Weather-Proof/6KV lightning protection/Surge protection AC24V/3000mA</p>	
2	VN-VTC-S31-C	<p>VidoNet 1/2.8 3MP(2048 x 1536 @25/30fps) Indoor HD Speed Dome camera f=5.5 ~ 110 mm lens, F1.6 ~ F3.5 Color:0.05 Lux @F1.2,AGC ON/B/W: 0.01Lux @F1.2,AGC ON,0Lux(IR LED ON) 20x Optical zoom ,360° endless rotation SD card local storage/Dual Stream/Mic in x 1/Mic out x 1 AC24V/3000mA</p>	






Index	Model No.	Product Description (NVR)	Photo
A	VidoNet Embedded Network Video Recorder (Non PoE)		Photo
1*	VN-VTN-204	Support 4Ch 3MP/2MP/960P/720P 30fps IP input Support 4Ch playback SATA x 1(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) DC12V	
2*	VN-VTN-208	Support 8Ch 3MP/2MP/960P/720P 30fps IP input Support 4Ch playback SATA x 2(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) DC12V	
3	VN-VTN-316	Support 16Ch 3MP/2MP/960P/720P 30fps IP input Support 4Ch playback SATA x 8(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) ATX (AC220V)	
4	VN-VTN-332-H.265	Support 32Ch 5MP/3MP/2MP/960P/720P 30fps IP input Support 16Ch playback SATA x 8(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) ATX (AC220V)	
5	VN-VTN-364-H.265	Support 32Ch 5MP/3MP/2MP/960P/720P 30fps IP input Support 16Ch playback SATA x 8(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) ATX (AC220V)	
6*	VN-VTN-232	Support 32Ch 3MP/2MP/960P/720P 30fps IP input Support 4Ch playback SATA x 2(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform)	



Index	Model No.	Product Description (NVR)	Photo
B	VidoNet Embedded Network Video Recorder (Built-in PoE)		Photo
1	VN-VTN-204P-H.265	Support 4Ch 5MP/3MP/2MP/960P/720P 30fps IP input Built-in 4 PoE Network Ports Support 4Ch playback SATA x 1(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform)	
2	VN-VTN-208P-H.265	Support 8Ch 5MP/3MP/2MP/960P/720P 30fps IP input Built-in 8 PoE Network Ports Support 4Ch playback SATA x 1(Up to 6TB) HDMI (4K)and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform)	
3	VN-VTN-208P2-H.265	Support 8Ch 5MP/3MP/2MP/960P/720P 30fps IP input Built-in 8 PoE Network Ports Support 8Ch playback SATA x 2(Up to 6TB) HDMI (4K)and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform)	
4	VN-VTN-316P-H.265	Support 16Ch 5MP/3MP/2MP/960P/720P 30fps IP input Built-in 16 PoE Network Ports Support 16Ch playback SATA x 4(Up to 6TB) HDMI (4K)and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform)	
5	VN-VTN-332P	Support 32Ch 3MP/2MP/960P/720P 30fps IP input Built-in 16 PoE Network Ports Support 16Ch playback SATA x 8(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform)	
6	VN-VTN-332P-H.265	Support 32Ch 5MP/3MP/2MP/960P/720P 30fps IP input Built-in 16 PoE Network Ports Support 16Ch playback SATA x 8(Up to 6TB) HDMI (4K)and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform)	



Index	Model No.	Product Description (AHD Camera 720P)	Photo
1	VN-VTC-E130MI-2.8 (New)	Image Sensor S3130 Video Output Mode (AHD/CVI/TVI/CVBS) f=2.8 mm Lens 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance IP66 & DC 12V (+/- 10%)	
2	VN-VTC-E130MI-3.6	1/4" CMOS Sensor AHD 1280 x 720P IR Water-proof Mini Eyeball Camera f = 3.6 mm Lens 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance IP66 & DC 12V (+/- 10%)	
3*	VN-VTC-B130MI-2.8	1/4" CMOS Sensor AHD 1280 x 720P IR Water-proof IR Bullet Camera f=2.8 mm Lens 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance IP66 & DC 12V (+/- 10%)	
4*	VN-VTC-B130MI-3.6	1/4" CMOS Sensor AHD 1280 x 720P IR Water-proof IR Bullet Camera f=3.6 mm Lens 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance IP66 & DC 12V (+/- 10%)	
5	VN-VTC-E130IR	1/4" CMOS Sensor AHD 1280 x 720P IR Water-proof IR Dome Camera f=2.8 - 12 mm Varifocal Lens 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance IP66 & DC 12V (+/- 10%)	

Index	Model No.	Product Description (AHD Camera 1080P)	Photo
1	VN-VTC-800D2.9WAHD (New)	1/2.7" CMOS Sensor + NVP2441H (AHD or 960H Mode) 1920 (H) x 1080 (V) at AHD Mode f=2.9mm (3MP) Fix Lens Up to 0.01Lux@F1.2 , 2D / 3D Noise Reduction , Support D-WDR Function DC 12V +/- 1V	
2	VN-VTC-800D2.9SAHD (New)	1/2.7" CMOS Sensor + NVP2441H (AHD or 960H Mode) 1920 (H) x 1080 (V) at AHD Mode f=2.9mm (3MP) Fix Lens Up to 0.01Lux@F1.2 , 2D / 3D Noise Reduction , Support D-WDR Function DC 12V +/- 1V	
3	VN-VTC-E200MI (New)	1/3" SONY CMOS Sensor AHD 1920 x 1080P IR Water-proof IR Dome Camera f = 2.8 mm Lens 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance & IP66 & DC 12V (+/- 10%)	
4	VN-VTC-E200MIS	1/3" SONY CMOS Sensor AHD 1920 x 1080P IR Water-proof IR Dome Camera f=3.6 mm Lens 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance & IP66 & DC 12V (+/- 10%)	
5	VN-VTC-B200IS	1/3" SONY CMOS Sensor AHD 1920 x 1080P IR Water-proof IR Dome Camera f=3.6 mm Lens 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance & IP66 & DC 12V (+/- 10%)	
6	VN-VTC-B200IRS	AHD 1920 x 1080P IR Water-proof IR Dome Camera 1/3" SONY CMOS Sensor f=2.8 - 12 mm Varifocal Lens & 0 Lux(Led On),ICR switch,Noise Reduction 20m IR Night view distance & IP66 & DC 12V (+/- 10%)	

Index	Model No.	Product Description (AHD DVR 720P)	Photo
1	VN-VTC-AH1301-4	Support 4Ch 720P AHD & 960H real time record Support 4Ch playback SATA x 1(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) DC12V	
2	VN-VTC-AH1301-8	Support 8Ch 720P AHD & 960H real time record Support 8Ch playback SATA x 1(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) DC12V	
3	VN-VTC-AH1301-16	Support 16Ch 720P AHD & 960H real time record Support 8Ch playback SATA x 1(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) DC12V	
4	VN-VTC-AH1302-16	Support 16Ch 720P AHD & 960H real time record Support 8Ch playback SATA x 2(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) DC12V	

Index	Model No.	Product Description (AHD DVR Hybrid 1080P)	Photo
1	VN-VTC-AH2001-4	Support 4Ch 1080P AHD & 960H real time record and 1 CH 1080P IP Camera Support 4Ch playback SATA x 1(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) DC12V	
2	VN-VTC-AH2001-8	Support 8Ch 1080P AHD & 960H real time record and 4 CH 3MP IP Camera Support 4Ch playback SATA x 1(Up to 6TB) HDMI and VGA output , USB x 2 ,DC12V Free APP for Android/iOS,NVMS(Management Paltform)	
3	VN-VTC-AH2002-16	Support 16Ch 1080P AHD & 960H real time record and 8 CH 3MP IP Camera Support 8Ch playback SATA x 2(Up to 6TB) HDMI and VGA output , USB x 2 ,DC12V Free APP for Android/iOS,NVMS(Management Paltform)	
4	VN-VTD-HB2004-32	Support 32Ch 1080P AHD & 960H real time record Support 16Ch playback SATA x 4(Up to 6TB) HDMI and VGA output , USB x 2 & ATX (AC220V) Free APP for Android/iOS,NVMS(Management Paltform)	
5	VN-VTD-HB2008-32	Support 32Ch 1080P AHD & 960H real time record Support 8Ch playback SATA x 8(Up to 6TB) HDMI and VGA output , USB x 2 Free APP for Android/iOS,NVMS(Management Paltform) ATX (AC220V)	

Index	Model No.	Product Description (AHD Camera 4MP)	Photo
1	VN-VTC-D400IS	4MP (2688 x 1520)real time image,high resolution,true color 1/3" CMOS Sensor f = 3.6mm Lens (2.8mm Optional) 0 Lux(Led On),ICR switch,Noise Reduction,20m IR Night view distance Support COC, Support 960H CVBS output IP66 & IK10 , DC 12V (+/- 10%)	
2	VN-VTC-B400IS	4MP (2688 x 1520)real time image,high resolution,true color 1/3" CMOS Sensor f = 3.6mm Lens (2.8mm Optional) 0 Lux(Led On),ICR switch,Noise Reduction,20m IR Night view distance Support COC, Support 960H CVBS output IP66 & IK10 , DC 12V (+/- 10%)	

Index	Model No.	Product Description (AHD DVR Hybrid 4MP)	Photo
1	VN-VTC-AH4001-4	4 CH AHD/TVI/CVI video input and 1 CH IPC 3MP/1080P/960P/720P/recording 4 CH 4MP / 3MP / 1080P / 720P / WD1 recording H.264 high profile compression 4 CH simultaneously palyback HDMI 2K output, true high resolution display SATA x 1(Up to 6TB)	
2	VN-VTC-AH4002-8	8 CH AHD/TVI/CVI video input and 4 CH IPC 3MP/1080P/960P/720P/recording 8 CH 4MP / 3MP / 1080P / 720P / WD1 recording H.264 high profile compression 8 CH simultaneously palyback HDMI 4K output, true high resolution display SATA x 2(Up to 6TB)	
3	VN-VTC-AH4002-16	16 CH AHD/TVI/CVI video input and 4 CH IPC 3MP/1080P/960P/720P/recording 16 CH 4MP / 3MP / 1080P / 720P / WD1 recording H.264 high profile compression 16 CH simultaneously palyback HDMI 4K output, true high resolution display SATA x 2(Up to 6TB)	